

UNCLASSIFIED

AD NUMBER

AD449859

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; AUG 1964. Other requests shall be referred to Army Missile Command, Redstone Arsenal, AL.

AUTHORITY

dsr/dod 1 aug 1966

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 449859

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

449859

CATALOGED BY DDC

449859

AS AD NO.

CONTRACT TECHNICAL NOTE

ELECTROMAGNETIC WAVE REFLECTION FROM A METAL-BACKED NON-UNIFORM PLASMA LAYER FOR NON-NORMAL INCIDENCE

CONTRACT NO. DA-04-495-ORD-3567(Z)
HYPERVELOCITY RANGE RESEARCH PROGRAM
A PART OF PROJECT "DEFENDER"



GM DEFENSE RESEARCH LABORATORIES

SANTA BARBARA, CALIFORNIA



AEROSPACE OPERATIONS DEPARTMENT



CTN64-06

AUGUST 1964

NOTICE

The information presented in this Technical Note is preliminary and should not be interpreted as representing the final opinion of GM Defense Research Laboratories or the author on the subject. Further, to expedite prompt distribution of the technical contents, no attempt at an editorial review has been made.

CONTRACT TECHNICAL NOTE

**ELECTROMAGNETIC WAVE REFLECTION FROM
A METAL-BACKED NON-UNIFORM
PLASMA LAYER FOR NON-NORMAL INCIDENCE**

Henry M. Musal, Jr.

**THIS RESEARCH WAS SUPPORTED BY THE
ADVANCED RESEARCH PROJECTS AGENCY**

**AND WAS MONITORED BY THE
U.S. ARMY MISSILE COMMAND
REDSTONE ARSENAL, ALABAMA**

GM DEFENSE RESEARCH LABORATORIES

SANTA BARBARA, CALIFORNIA



AEROSPACE OPERATIONS DEPARTMENT

**CONTRACT NO. DA-04-495-ORD-3567(Z)
HYPERVELOCITY RANGE RESEARCH PROGRAM
A PART OF PROJECT "DEFENDER"**

DDC AVAILABILITY NOTICE

Qualified requesters may obtain
copies of this report from DDC

CTN64-06

AUGUST 1964

CONTRACT TECHNICAL NOTE

ELECTROMAGNETIC WAVE REFLECTION FROM
A METAL-BACKED NON-UNIFORM
PLASMA LAYER FOR NON-
NORMAL INCIDENCEHenry M. Musal, Jr.
August, 1964INTRODUCTION

The purpose of this note is to document a technique for the calculation of the reflection coefficients for a plane transverse electromagnetic wave incident non-normally on a non-uniform plasma layer with a metal-backing wall. It is assumed that the plasma properties (plasma frequency and electron collision frequency) vary spatially only in the direction normal to the metal wall. The plasma layer is treated as a spatially non-uniform lossy dielectric material. The situation in which the incident electromagnetic wave is normally incident has been extensively treated in the literature*. For non-normal incidence, it is most convenient to consider an arbitrarily polarized incident electromagnetic wave to be composed of TE(transverse electric) and TM(transverse magnetic) modes. The reflection coefficient for each of these different modes is then found separately. This approach greatly simplifies the analysis.

* See, for example, Zivanovic⁽¹⁾.

THEORY

The geometry of the situation is shown in Figure 1. In the free-space region the incident electromagnetic wave propagates toward the plasma boundary at the angle θ_i to the normal, and the reflected electromagnetic wave propagates away from the plasma boundary also at the angle θ_i to the normal. These waves are both either TE or TM modes, that is, either the electric or the magnetic field is directed in the y-direction. Correspondingly, in the non-uniform plasma region the electric or magnetic field has only a y-direction component. These two different field configurations lead to two different reflection coefficients, which are most expeditiously found by two different approaches.

TE Mode Reflection Coefficient

The incident electromagnetic wave, for the TE mode, is given by

$$\vec{E}_i = \vec{1}_y E_i e^{-jk_r(x \sin \theta_i + z \cos \theta_i)} \quad (1)$$

$$\begin{aligned} \vec{H}_i &= (-\vec{1}_x \cos \theta_i + \vec{1}_z \sin \theta_i) \\ &\left(\frac{\epsilon_r}{\mu_r}\right)^{1/2} E_i e^{-jk_r(x \sin \theta_i + z \cos \theta_i)} \end{aligned} \quad (2)$$

where the time variation factor $\exp(j\omega t)$ has been suppressed, \vec{E}_i

and \vec{H}_i are the electric and magnetic field intensities, \vec{i}_x , \vec{i}_y and \vec{i}_z are the x, y and z unit vectors, E_i is the complex amplitude of the incident wave, k_v is $2\pi/\lambda_v$ where λ_v is the wavelength of the incident wave in the free-space region, θ_i is the angle of incidence, and ϵ_v and μ_v are the free-space capacity and inductivity.

The reflected electromagnetic wave is given by

$$\vec{E}_r = \vec{i}_y E_r e^{-jk_v(x \sin \theta_i - z \cos \theta_i)} \quad (3)$$

$$\vec{H}_r = (\vec{i}_x \cos \theta_i + \vec{i}_z \sin \theta_i) \left(\frac{\epsilon_v}{\mu_v} \right)^{1/2} E_r e^{-jk_v(x \sin \theta_i - z \cos \theta_i)} \quad (4)$$

where the time variation factor $\exp(j\omega t)$ has been suppressed, \vec{E}_r and \vec{H}_r are the electric and magnetic field intensities, and E_r is the complex amplitude of the reflected wave. The TE mode reflection coefficient R_{TE} is given by

$$R_{TE} \equiv \frac{E_r}{E_i} \quad (5)$$

In the non-uniform plasma layer Maxwell's equations, with the time dependence $\exp(j\omega t)$, are

$$\nabla \times \vec{E} = -j\omega \mu_v \vec{H} \quad (6)$$

$$\nabla \times \vec{H} = j\omega \epsilon_r \epsilon \vec{E} \quad (7)$$

$$\nabla \cdot \epsilon \vec{E} = 0 \quad (8)$$

$$\nabla \cdot \vec{H} = 0 \quad (9)$$

where ϵ is the effective dielectric constant of the plasma, which varies spatially in the z-direction, and ω is the angular frequency of the time variation of the fields. The effective dielectric constant of the plasma ϵ is taken to be

$$\epsilon = 1 - \frac{\Omega_p^2}{1 - j\Omega_c} \quad (10)$$

where Ω_p and Ω_c are the normalized plasma and electron collision frequencies, respectively. In general, both Ω_p and Ω_c may be functions of position in the z-direction. The wave equation for \vec{E} is found to be

$$\nabla^2 \vec{E} + k_r^2 \epsilon \vec{E} + \nabla \left[\frac{1}{\epsilon} (\nabla \epsilon) \cdot \vec{E} \right] = 0 \quad (11)$$

where the relationship $k_r^2 = \omega^2 \mu_r \epsilon_r$ has been used to simplify the result.

For the TE mode, \vec{E} has only a y-direction component, and $\nabla\epsilon$ has only a z-direction component, hence the vector wave equation can be reduced to a single scalar partial differential equation for the y-direction component of the electric field intensity E_y (which is the total electric field in the plasma layer). This equation is

$$\partial_x^2 E_y + \partial_z^2 E_y + k_r^2 \epsilon E_y = 0 \quad (12)$$

Recognizing⁽²⁾ that all fields must vary periodically in the x-direction according to the factor $\exp(-jk_v x \sin \theta_i)$, this partial differential equation can be reduced to the ordinary differential equation

$$\frac{d^2 u}{d s^2} + k_r^2 (\epsilon - \sin^2 \theta_i) u = 0 \quad (13)$$

where

$$E_y = A u e^{-jk_v x \sin \theta_i} \quad (14)$$

and where the independent variable z has been transformed to a new independent variable s , (where $s = h - z$), which is measured outward from the metal wall as shown in Figure 1. The associated magnetic field intensity in the plasma layer is

$$\vec{H} = \frac{A}{-j\omega\mu_r} \left[\vec{I}_x \frac{du}{ds} + \vec{I}_z (-jk_r \sin\theta_i) u \right] e^{-jk_r x \sin\theta_i} \quad (15)$$

which has both x and z -direction components.

The appropriate boundary conditions are zero tangential electric field at the metal wall, and continuous tangential components of electric and magnetic fields at the interface between the free-space region and the plasma layer. These boundary conditions lead to the constraints

$$u|_{s=0} = 0 \quad (16)$$

$$E_i + E_r = A u_h \quad (17)$$

$$\cos\theta_i E_i - \cos\theta_i E_r = -j \frac{A}{k_r} u_h' \quad (18)$$

where u_h and u_h' are the values of u and du/ds at $s=h$.

These equations can be solved to give the TE mode reflection coefficient

R_{TE} in the form

$$R_{TE} = \frac{u_h \cos\theta_i + j \frac{u_h'}{k_r}}{u_h \cos\theta_i - j \frac{u_h'}{k_r}} \quad (19)$$

where u satisfies equation (13) with the initial condition given in equation (16).

TM Mode Reflection Coefficient

The incident electromagnetic wave, for the TM mode, is given by

$$\vec{H}_i = \vec{1}_y H_i e^{-jk_r(x \sin \theta_i + z \cos \theta_i)} \quad (20)$$

$$\begin{aligned} \vec{E}_i &= (\vec{1}_x \cos \theta_i - \vec{1}_z \sin \theta_i) \\ &\quad \left(\frac{\mu_r}{\epsilon_r}\right)^{1/2} H_i e^{-jk_r(x \sin \theta_i + z \cos \theta_i)} \end{aligned} \quad (21)$$

where the time variation factor $\exp(j\omega t)$ has been suppressed and H_i is the complex amplitude of the incident wave. The reflected electromagnetic wave is given by

$$\vec{H}_r = \vec{1}_y H_r e^{-jk_r(x \sin \theta_i - z \cos \theta_i)} \quad (22)$$

$$\begin{aligned} \vec{E}_r &= -(\vec{1}_x \cos \theta_i + \vec{1}_z \sin \theta_i) \\ &\quad \left(\frac{\mu_r}{\epsilon_r}\right)^{1/2} H_r e^{-jk_r(x \sin \theta_i - z \cos \theta_i)} \end{aligned} \quad (23)$$

where the time variation factor $\exp(j\omega t)$ has been suppressed and H_r is the complex amplitude of the reflected wave. The TM mode reflection coefficient R_{TM} is given by

$$R_{TM} = \frac{H_r}{H_i} \quad (24)$$

In the non-uniform plasma layer, the wave equation for \vec{H} is found to be

$$\nabla^2 \vec{H} + k_r^2 \epsilon \vec{H} + \frac{1}{\epsilon} (\nabla \epsilon) \times (\nabla \times \vec{H}) = 0 \quad (25)$$

For the TM mode, \vec{H} has only a y-direction component, and $\nabla \epsilon$ has only a z-direction component, hence the vector wave equation can be reduced to a single scalar partial differential equation for the y-direction component of the magnetic field intensity H_y (which is the total magnetic field in the plasma layer). This equation is

$$\begin{aligned} \partial_x^2 H_y + \partial_z^2 H_y + k_r^2 \epsilon H_y \\ - \frac{1}{\epsilon} \frac{d\epsilon}{dz} \partial_z H_y = 0 \end{aligned} \quad (26)$$

Again, since all fields must vary periodically in the x-direction according

to the factor $\exp(-jk_r x \sin \theta_i)$, this partial differential equation can be reduced to the ordinary differential equation

$$\frac{d^2 N}{dS^2} + k_r^2 (\epsilon - \sin^2 \theta_i) N - \frac{1}{\epsilon} \frac{d\epsilon}{dS} \frac{dN}{dS} = 0 \quad (27)$$

where

$$H_y = B N e^{-jk_r x \sin \theta_i} \quad (28)$$

and where the independent variable z has been transformed to a new independent variable S , (where $S = h - z$), which is measured outward from the metal wall as shown in Figure 1. The associated electric field intensity in the plasma layer is

$$\vec{E} = \frac{B}{j\omega\epsilon_r\epsilon} \left[+\vec{I}_x \frac{dN}{dS} + \vec{I}_z (-jk_r \sin \theta_i) N \right] e^{-jk_r x \sin \theta_i} \quad (29)$$

which has both x and z -direction components.

Application of the boundary conditions leads to the constraints

$$\left. \frac{dn}{ds} \right|_{s=0} = 0 \quad (30)$$

$$H_i + H_r = B n_h \quad (31)$$

$$\cos \theta_i H_i - \cos \theta_r H_r = -j \frac{B}{\epsilon_h k_r} n_h' \quad (32)$$

where n_h , n_h' and ϵ_h are the values of n , dn/ds and ϵ at $s = h$. These equations can be solved to give the TM mode

reflection coefficient R_{TM} in the form

$$R_{TM} = \frac{n_h \cos \theta_i + j \frac{n_h'}{\epsilon_h k_r}}{n_h \cos \theta_i - j \frac{n_h'}{\epsilon_h k_r}} \quad (33)$$

where n satisfies equation (27) with the initial condition given in equation (30).

RESULTS

This note shows that both the TE and TM mode electromagnetic wave reflection coefficients for oblique incidence on a metal-backed plasma

layer, which is spatially non-uniform in the direction normal to the layer, can be found when the functional variation of the plasma properties is known. This is done by solution of a pair of ordinary second-order linear differential equations, with given initial conditions at the metal wall, over the interval defined by the thickness of the plasma layer. The differential equations are exact, hence the accuracy of the results depends only on the accuracy of the numerical solution of these equations.

REFERENCES

1. S. Zivanovic, "A Numerical Method for the Determination of the Transmission and Reflection Coefficients of a Non-Uniform Plasma Slab", Technical Report TR62-209J, December 1962, GM Defense Research Laboratories, General Motors Corporation, Santa Barbara, California
2. G. F. Miller, III, "Propagation of Electromagnetic Waves in a Nonuniformly Ionized Medium", Physics of Fluids, Vol. 5, No. 8, August 1962, pp. 899-907.




Figure 1 Geometry of the Electromagnetic Wave-
Nonuniform Plasma Layer
Reflection Problem

DISTRIBUTION LIST
for Analysis Reports on the
HYPERVELOCITY RANGE RESEARCH PROGRAM

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Director		U. S. Air Force	
Advanced Research Projects Agency		Ballistic Systems Division	
Washington 25, D. C.		AF Unit Post Office	
ATTN: F. Koether	1 - 3	Los Angeles 45, California	
ATTN: E. Haynes	4	ATTN: Major W. Levy	51
ATTN: C. McLain	5	ATTN: Lt. K. G. Jefferson	52
ATTN: Major J. Kiernan	6	HQ BSD (AFSC)	
Aerojet-General Corporation		AF Unit Post Office	
P. O. Box 296		Los Angeles 45, California	
Azusa, California		ATTN: BSRVD	53
ATTN: Technical Library	7	USAF Cambridge Research Laboratories	
Aeronutronics Division, Ford Motor Co.		Laurence Hanscom Field	
Ford Road		Bedford, Massachusetts	
Newport Beach, California		ATTN: CRRELRL, Stop 29	54
ATTN: Technical Information Services	8	Director	
ATTN: R. Hoglund	9	USAF Office of Scientific Research	
Aerospace Corporation		Washington 25, D. C.	
2400 E. El Segundo Blvd		ATTN: Mechanics Division/	55
El Segundo, California		Major Terrell	
ATTN: Manager of Penetration Aids	10	Director	
Aerospace Corporation		Ames Research Center	
P. O. Box 95085		Moffett Field, California	
Los Angeles 45, California		ATTN: H. Allen	56
ATTN: J. Logan	11	Applied Physics Laboratory	
Aerospace Corporation		The John Hopkins University	
San Bernardino, California		8621 Georgia Avenue	
ATTN: Mr. R. Fowler	12	Silver Spring, Maryland	
ATTN: Mr. Howard Meyers	13-42	ATTN: G. Seielstad	57
Avco-Everett Research Laboratory		Applied Physics Laboratory	
2385 Revere Beach Parkway		Sylvania Elec. Products	
Everett 49, Massachusetts		Waltham, Massachusetts	
ATTN: Dr. Bennett Kivel	43	ATTN: R. Row	58
ATTN: Technical Library	44	Armour Research Foundation	
Avco Research and Advanced Development		10 W. 35th Street	
Wilmington, Massachusetts		Chicago 16, Illinois	
ATTN: Dr. A. Pallone	45	ATTN: Fluid Dynamics Research	59
ATTN: Dr. W. E. Gibson	46	Division	
ATTN: Dr. J. Ekerman	47	Commanding General	
Bell Telephone Laboratories		U. S. Army Air Defense Command	
Murray Hill, New Jersey		Colorado Springs, Colorado	
ATTN: Dr. I. Pelech	48	ATTN: Advanced Projects Division, G-3	60
ATTN: Dr. S. P. Morgan	49		
ATTN: Dr. S. J. Buchsbaum	50		

DISTRIBUTION LIST (continued)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Commanding General U. S. Army Ballistics Research Laboratories Aberdeen Proving Gound, Maryland ATTN: C. H. Murphy ATTN: B. J. Karpov	61 62	Avco Corporation Research and Advanced Development Division Wilmington, Massachusetts ATTN: Technical Library ATTN: Dr. Wentink	76 77
Commanding General U. S. Army Elec. and Communications Command Research and Development Fort Monmouth, New Jersey	63	Special Projects Office Department of The Navy Washington 25, D. C. ATTN: Martin Bloom/SP-272	78
Commanding General U. S. Army Materiel Command Washington 25, D. C.	64	Barnes Engineering Company 30 Commerce Road Stamford, Connecticut ATTN: H. Yates	79
Commander U. S. Army Missile Command Redstone Arsenal, Alabama ATTN: AMSMI-RB ATTN: AMSMI-RRX ATTN: AMSMI-RNR ATTN: AMCPM-ZER-R	65 66 67 68	Battelle Memorial Institute 505 King Avenue Columbus 1, Ohio ATTN: Battelle-DEFENDER	80
Security Office, Army Missile Command Pacific Field Office Box 56, Navy 824 c/o FPO, San Francisco, California ATTN: Dr. S. Edelberg	69	Bell Telephone Laboratories, Inc. Whippany, New Jersey ATTN: C. W. Hoover, Room 2B-105 ATTN: C. E. Paul ATTN: John McCarthy	81 82 83
Commanding General U. S. Army Research and Development Washington 25, D. C. ATTN: Intl. Division ATTN: Physical Sciences Division	70 71	Bendix Corporation Systems Division 3300 Plymouth Road Ann Arbor, Michigan ATTN: Systems Analysis and Math Dept. ATTN: Flight Sciences Department	84 85
Commanding Officer U. S. Army Signal Missile Support Agency White Sands Missile Range, New Mexico ATTN: SIGWS-MM-1 ATTN: MEW	72 73	Boeing Airplane Company P. O. Box 3707 Seattle, Washington ATTN: Org. 2-5732/J. Klaimon	86
U. S. Army Technical Intelligence Agency Arlington Hall Station Arlington 12, Virginia ATTN: ORDLI	74	Brown Engineering Company Huntsville, Alabama ATTN: Technical Library	87
ARO, Inc. von Karman Facility Tullahoma, Tennessee ATTN: J. Lukasiewicz	75	California Institute of Technology Pasadena, California ATTN: Prof. L. Lees	88
		Central Intelligence Agency 2930 E Street, N. W. Washington, D. C. ATTN: OCR Standard Distribution	89-91

DISTRIBUTION LIST (continued)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Communication and Propagation Laboratory Stanford Research Institute Menlo Park, California ATTN: Mr. Ray L. Leadabrand, Head Propagation Group	92	Geophysics Corporation of America Burlington Road Bedford, Massachusetts	123
ATTN: Dr. Carson Flammer	93	Heliodyne Corporation 2365 Westwood Blvd Los Angeles 64, California	124
Defense Documentation Center Cameron Station Alexandria, Virginia	94-113	Institute for Defense Analyses 1666 Connecticut Avenue N.W. Washington 9, D. C. ATTN: Dr. J. Menkes	125
Cornell Aeronautical Laboratory 4455 Genesee Street Buffalo 21, New York ATTN: J. Lotsof	114	ATTN: Dr. L. Biberman	126
ATTN: W. Wurster	115	ATTN: Dr. R. Fox	127
ATTN: Applied Physics Dept.	116	ATTN: Dr. J. Martin	128
Defense Research Corporation 6300 Hollister Avenue, Goleta, California ATTN: W. Short	117	ATTN: Mr. D. Katcher, JASON Library	129
Director Electromagnetic Warfare Laboratory Wright-Patterson Air Force Base Dayton, Ohio ATTN: ASRN/W. Bahret	118	Institute of Science and Technology The University of Michigan P. O. Box 618 Ann Arbor, Michigan ATTN: BAMIRAC Library	130
Electro-Optical Systems, Inc. 300 N. Halstead Street Pasadena, California ATTN: R. Denison	119	Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, California ATTN: H. Denslow	131
General Applied Sciences Laboratories Merrick and Stewart Avenues Westbury, Long Island, New York ATTN: M. Bloom	120	ATTN: Library	132
General Dynamics Corporation Astronautics Division San Diego, California ATTN: Chief Librarian, Mail Zone 6-157	121	Kaman Nuclear Division Colorado Springs, Colorado ATTN: A. Bridges	133
General Electric Company Re-entry Vehicles Division 3198 Chestnut Street Philadelphia, Pennsylvania ATTN: L. I. Chaseen, Room 3446	122	Director Langley Research Center Langley Field, Virginia ATTN: W. Erickson	134
		ATTN: R. L. Trimpi	135
		Lockheed Corporation Missiles and Space Division Sunnyvale, California ATTN: Ray Munson	136
		Melpar, Inc. Applied Science Division 11 Galen Street Watertown 72, Massachusetts ATTN: Librarian	137

DISTRIBUTION LIST (continued)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Martin Aircraft Company Orlando, Florida ATTN: J. Mays	138	Purdue University School Aero and Engineering Sciences La Fayette, Indiana ATTN: I. Kvakovsky	151
Director Marshall Space Flight Center Huntsville, Alabama ATTN: M-AERO-TS	139	Radio Corporation of America Missiles and Surface Radar Division Moorestown, New Jersey	152
Massachusetts Institute of Technology Lincoln Laboratory P. O. Box 73 Lexington 73, Massachusetts ATTN: M. Herlin ATTN: R. Slattery ATTN: V. Guethlen	140 141 142	The Rand Corporation 1700 Main Street Santa Monica, California ATTN: Library	153
Chief U. S. Navy Bureau of Weapons Washington 25, D. C. ATTN: RMWC-322	143	Raytheon Manufacturing Company Missile Systems Division Bedford, Massachusetts ATTN: I. Britton, Librarian	154
Chief of Naval Operations Washington 25, D. C. ATTN: OP-07T10	144	Rome Air Development Center Griffiss Air Force Base Rome, New York ATTN: P. Sandler	155
Commander U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Maryland ATTN: Technical Library	145	The Martin Company Aerospace Division, Mail No. T-38 P. O. Box 179, Denver, Colorado 80201 ATTN: R. E. Compton, Jr.	156
Director U. S. Naval Research Laboratory Washington 25, D. C. ATTN: Code 2027	146	Space Technology Laboratories, Inc. 1 Space Park Redondo Beach, California ATTN: Leslie Hromas	157
New York University Department of Aero Engineering University Heights New York 53, New York ATTN: L. Arnold	147	The Warner and Swasey Company Control Instrument Division 32-16 Downing Street Flushing 54, New York	158
North American Aviation Space and Information Systems Division 12214 Lakewood Blvd Downey, California ATTN: E. Allen	148	University of California San Diego, California ATTN: Prof. N. M. Kroll	159
Princeton University Princeton, New Jersey ATTN: Prof. E. Frieman ATTN: Prof. S. Bogdonoff	149 150	University of California Lawrence Radiation Laboratory Livermore, California ATTN: C. Craig	160
		Scientific and Technical Information Facility P. O. Box 5700 Bethesda, Maryland ATTN: NASA Representative (SAK/DL-639)	161, 162

DISTRIBUTION LIST (Concluded)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
General Electric Company Re-entry Systems Department Missile and Space Division P. O. Box 8555 Philadelphia, Pennsylvania ATTN: Mr. H. W. Ridyard	163	* Commanding Officer U. S. Army Missile Command Redstone Arsenal, Alabama ATTN: SMIDW-B1 (C)	168
University of Michigan Radiation Laboratory 201 Catherine Ann Arbor, Michigan ATTN: R. J. Leite	164	**British Joint Mission British Embassy 3100 Massachusetts Avenue, N. W. Washington, D. C. ATTN: Mr. F. I. Reynolds, Defense Research Staff	169
Valley Forge Space Technical Center General Electric Company P. O. Box 8555 Philadelphia 1, Pennsylvania ATTN: J. Farber	165	**Australian Embassy 2001 Connecticut Avenue N. W. Washington, D. C. ATTN: D. Barnsley, Defense Research and Development Rep.	170
Director Weapons Systems Evaluation Group Pentagon, Room 1E-800 Washington 25, D. C.	166	*University of Toronto Department of Electrical Engineering Toronto, Ontario, Canada ATTN: Mr. H. Treial, Research Associate	171
U. S. Army Liaison Office Canadian Armament Research and Development Establishment P. O. Box 1427 Quebec, P. Q., Canada ATTN: Lt. Col. E. W. Kreischer	167	Capt. L. L. Schoen, USAF USAF Technical Representative c/o GM Defense Research Laboratories GM Defense Research Laboratories	172 173 and above

* Unclassified reports only.

** Research reports on hypervelocity ranges and air and contaminant chemistry only – not included for analytical reports on U. S. missile data or classified reports.

Additional Distribution for Semiannual Reports only:

Office of Naval Research
Department of the Navy
Washington 25, D. C.
ATTN: Dr. S. Silverman, Science Director 1 copy
ATTN: Dr. F. Isakson, Physics Branch 1 copy
ATTN: Mr. M. Cooper, Fluid Dynamics Branch 1 copy

UNCLASSIFIED

UNCLASSIFIED